



## FAST GRUNT M

### priming plaster coat under mineral and acrylic plasters

- APPLICATION** A well coating priming plaster containing quartz molecules is a ready for use preparation designed for preparing the base under mineral and acrylic plasters. Owing to its distinctive features it is recommended for priming all kinds of concrete, ceramic and cement-lime surfaces which then will be plastered. It can be applied both inside as well as outside buildings.
- CHARACTERISTICS** **FAST GRUNT M** is characteristic for its perfect adhesive and well-coating features as well as great penetrating abilities. It is water-proof, freeze-resistant and steam-permeable, lowers the absorptivity of the base and creates the optimum adhesion of the outer layer of the base. It is also resistant to the reaction of alkalies.
- PREPARATION OF** **FAST GRUNT M** can be applied on any dry bases cleaned of dust, wax, grease, oils, lubricants and non-permeable paint coats. In case of weak and absorbable surfaces, before applying **FAST GRUNT M**, the base should be first primed with **FAST GRUNT G**.
- PREPARATION AND** Apply **FAST GRUNT M** on a ready, primed and dry surface with a brush or a roller at the temperature of from +5°C to +25°C. Plastering can be started not earlier than 24 hours after treating the base with **FAST GRUNT M**.

- EFFICIENCY** The average use is approximately 0,35 kg/m<sup>2</sup>.
- STORAGE** Store in tightly closed packages at the temperature of from +5°C up to +25°C. Suitability for use: 12 months.
- TECHNICAL SPECIFICATIONS** Temperature of the base: **from + 5°C to + 25° C**  
Use of the base: **after 24 hours**  
Density: **approximately 1,60 kg/dm<sup>3</sup>**
- PACKAGES** Plastic buckets of 6,4 kg and 16 kg.  
Pallets: 512 kg in the plastic buckets of 6,4 kg (80 items)  
704 kg in the plastic buckets of 16 kg (44 items)



## **FAST GRUNT M** **priming plaster coat under mineral and acrylic plasters**

### **STANDARDS / NORMS**

Technical Approval ITB – AC 020: AT-15-3513/2005, AT-15-6141/2005  
Sanitary Certificate issued by the State Sanitary Department no HK/B/ 2799/01/2001.

### **NOTE**

The range of the product use recommended and defined in these instructions does not relieve the user/contractor from the obligation of carrying out works following both building principles as well as labour safety regulations.

P.W. FAST guarantees and shall be liable for the product quality, however it cannot control methods in which the product was used and under what conditions.

**An Element of insulating systems FAST SA, FAST SM, FAST W, FAST W-G.**