



## FAST GRUNT U

### universal wall and floor priming preparation

#### APPLICATION

**FAST GRUNT U** is a ready for use preparation for priming and leveling out the absorptivity of different surfaces. It is perfect to be applied on concrete and gas-concrete bases, as well as on gypsum and gypsum-cardboards, cement and cement-lime plasters. It can be used both inside and outside buildings. It makes a perfect basis to be then treated with paints, putty, adhesive and leveling out plasters as well as to be covered with wallpapers or cement flooring. It increases the adhesion of finishing materials and lowers material dusting. One of its extraordinary features is the fact that it inhibits the growth of mould and microorganisms on the primed bases.

#### CHARACTERISTICS

**FAST GRUNT U** does not contain solvents, it is non-flammable, water-diluted, odour-free, environmentally-friendly and can be applied both inside as well as outside buildings. The concentrate makes the base faster, regulates the base absorptivity process and lowers the use of paint. After drying up it is completely transparent and steam-permeable. It contains an agent preventing the growth of mould and microorganisms.

#### PREPARATION OF

**FAST GRUNT U** can be applied on a base which is dry, free from any impurities such as dust, wax, grease, oil, lubricants and non-permeable paint coats. In case there is mould, they should be first treated with **FAST MUR**.

#### PREPARATION

The preparation can be applied with a brush or a roller onto the base with the temperature of from +5°C to +25°C. In case of a very absorptive, worn out or pouring out base it is recommended to prime it first with a deeply penetrating preparation **FAST GRUNT G**. The base primed with **FAST GRUNT U** is ready for further working after approximately 24 hours after priming. In case there has been a skin contact, rinse with water.

#### EFFICIENCY

The use of the emulsion depends greatly on the degree of absorptivity of the base and is approximately 0,05 – 0,25 kg/m<sup>2</sup>.

#### STORAGE

Store in tightly closed packages at the temperature of from +5°C up to +25°C. Suitability for use: 12 months.



## FAST GRUNT U

### universal wall and floor priming preparation

#### TECHNICAL SPECIFICATIONS

Temperature of the base: **from + 5°C to + 25°C**  
Use of the base: **after 24 hours**  
Density: **approximately 1,02 kg/ dm<sup>3</sup>**  
Temperature resistance: **from -20°C up to + 70°C**

#### PACKAGES

Containers 2kg, 5 kg and 10 kg.  
Pallets: 480 kg in 2kg containers ( 240 items)  
540 kg in 5kg containers (108 items)  
360 kg in 10 kg containers (36 items)

#### STANDARDS / NORMS

Manufactured according to: PN-C-81906:2003  
Sanitary Certificate issued by the State Sanitary Department no HK/B/ 1432/01/2003.

#### NOTE

The range of the product use recommended and defined in these instructions does not relieve the user/contractor from the obligation of carrying out works following both building principles as well as labour safety regulations.  
P.W. FAST guarantees and shall be liable for the product quality, however it cannot control methods in which the product was used and under what conditions.