



FAST FOLIA

sealing anti-moisture agent



- APPLICATION** **FAST FOLIA** is a product made on the base of plastics, which after having been applied makes a moisture impermeable coat, perfectly adhering to such bases as: gypsum cardboards, chipboards, cement-lime plasters, concrete, structural tiles. After drying up it makes a ready undersurface for such finishing materials as: glaze, terracotta, wooden and panel flooring, synthetic floor finishes. It is designed for damp and wet rooms with a pressure-less reaction of water. It is also suitable for sealing floor/wall connections.
- CHARACTERISTICS** **FAST FOLIA** is a high quality mixture of a specially selected resin, fillers and modifiers. It can be characterized for its great adherence, elasticity, water resistance. It is easy to apply. Apart from the above features, **FAST FOLIA** is fungicidal.
- PREPARATION OF** The base under **FAST FOLIA** should be cleaned of dust, grease, dirt, salt blooms, remains weakly adhering to the base. Surfaces strongly absorptive, weak, dusting should be primed with a deeply priming product **FAST GRUNT G**.
- INSTRUCTIONS** **FAST FOLIA** is a ready for use product. It cannot be mixed with other products or dilute. Before starting to apply the plaster, the contents of each package should be mixed (stirred) with a slow-running drill in order to make the consistence even. Apply the coat with a roller, float or a trowel. Finish works cannot be started earlier than 24 hours after applying the last coat.
- EFFICIENCY** Depending on the base up to 1,10 kg/m² (on a wall), 1,40 kg/m² (on a floor).
- STORAGE** Store in tightly closed packages in a dry room at the temperature of +5°C up to 25°C. Suitability for use: 12 months from production date (see the package).
- PACKAGES** Buckets 5kg and 10kg.
- STANDARDS / NORMS** Sanitary Certificate issued by the State Sanitary Department no HK/B/0298/01/2004.



FAST FOLIA

sealing anti-moisture agent



NOTE

The range of the product use recommended and defined in these instructions does not relieve the user/contractor from the obligation of carrying out works following both building principles as well as labour safety regulations.
P.W. FAST guarantees and shall be liable for the product quality, however it cannot control methods in which the product was used and under what conditions.