



FAST GRUNT K

protective agent for pitchers (Belgian blocks), concrete as well as mineral, porous surfaces

APPLICATION **FAST GRUNT K** is a ready for use priming emulsion which protects surfaces of mineral, porous bases such as concrete, pitchers, non-glazed terracotta against stains made with oil, fat, coffee, tea, wine, etc., which deteriorate the look of the surface. It can be applied both inside as well as outside buildings.

CHARACTERISTICS Owing to its distinctive features, **FAST GRUNT K**, in the first period after having been applied, protects surfaces against water absorbability. Furthermore, it is characteristic for the increased resistance to dirt and stains. It is UV resistant.

PREPARATION OF **FAST GRUNT K** can be applied on any dry bases cleaned of dust, wax, grease, oils, lubricants, moss and weeds.

PREPARATION AND The emulsion can be applied with a brush or a roller onto the base with the temperature of +5°C to +25°C. After 4 months it is recommended to reapply the emulsion.

EFFICIENCY The use of the emulsion greatly depends on the degree of absorptivity of the base and is approximately 0,15 – 0,25 l/m².

STORAGE Store in tightly closed packages at the temperature of from +5°C up to +25°C. Suitability for use: 12 months

TECHNICAL SPECIFICATIONS

Temperature of the base:	from + 5°C to + 25° C
Use of the base:	after 12 hours
Time of drying up:	approximately 2 hours
Density:	approximately 1kg/ dm³



FAST GRUNT K

protective agent for pitchers (Belgian blocks), concrete as well as mineral, porous surfaces

PACKAGES

Containers 5l and 10l.

Pallets: 540 kg in 5l containers (108 items)

360 kg in 10 l containers (36 items)

STANDARDS / NORMS

Manufactured according to: PN-C-81906:2003

Sanitary Certificate issued by the State Sanitary Department no HK/B/ 1017/01/2001.

NOTE

The range of the product use recommended and defined in these instructions does not relieve the user/contractor from the obligation of carrying out works following both building principles as well as labour safety regulations.

P.W. FAST guarantees and shall be liable for the product quality, however it cannot control methods in which the product was used and under what conditions.