



FAST GRUNT P

wall and floor surface-priming concentrate

APPLICATION **FAST GRUNT P** is a ready for use priming emulsion to be applied on all absorptive and porous surfaces such as: gypsum boards, cardboards, gypsum plasters, cement and cement-lime plasters, concrete bases, gas concrete, ceramics, etc.

CHARACTERISTICS **FAST GRUNT P** does not contain solvents, it is non-flammable, water-diluted, odour-free, environmentally-friendly and can be applied both inside as well as outside buildings. The concentrate makes the base faster, regulates the base absorptivity process and lowers the use of paint. After drying up it is completely transparent and steam-permeable.

PREPARATION OF **FAST GRUNT P** can be applied on a base which is dry, free from any impurities such as dust, wax, grease, oil, lubricants and non-permeable paint coats.

PREPARATION The emulsion must be applied with a brush or a roller onto the base with the temperature of from +5°C to +25°C. In case of a very absorptive or worn out base it is recommended to be primed twice (the second time with a diluted concentrate onto the still wet base). The concentrate should be water diluted at the 1:1 ratio. Do not dilute the concentrate when the base is less absorptive. The base primed with **FAST GRUNT P** is ready for further working approximately 24 hours after priming. In case there has been a skin contact, rinse with water.

EFFICIENCY The use of the emulsion depends greatly on the degree of absorptivity of the base and is approximately 0,05 – 0,25 kg/m².

STORAGE Store in tightly closed packages at the temperature of from +5°C up to +25°C. Suitability for use: 12 months.

TECHNICAL SPECIFICATIONS

Temperature of the base:	from + 5°C to + 25°C
Use of the base:	after 24 hours
Density:	approximately 1,02 kg/dm³
Temperature resistance:	from -20°C up to + 70°C



FAST GRUNT P

wall and floor surface-priming concentrate

PACKAGES

Containers 2kg, 5 kg and 10 kg.
Pallets: 480 kg in 2kg containers (240 items)
540 kg in 5kg containers (108 items)
360 kg in 10kg containers (36 items)

STANDARDS / NORMS

Manufactured according to: PN-C-81906:2003
Sanitary Certificate issued by the State Sanitary Department no HK/B/ 1697/01/2004.

NOTE

The range of the product use recommended and defined in these instructions does not relieve the user/contractor from the obligation of carrying out works following both building principles as well as labour safety regulations.
P.W. FAST guarantees and shall be liable for the product quality, however it cannot control methods in which the product was used and under what conditions.