



FAST RENO-ROOF renovating-protecting roof paint

APPLICATION

FAST RENO-ROOF is a professional paint for roof renovation. Carefully selected recipe of the paint makes it possible to renovate bituminous undulated panels, flat asbestos-cement panels, concrete and ceramic roofing tiles etc. **RENO-ROOF** not only improves the appearance of the surfaces undergoing renovation, but protects them at the same time. It is available in red, brown, black, green (mat or glossy).

CHARACTERISTICS

FAST RENO-ROOF is a professional paint produced on the base of acrylic resins and styrene-acrylic dispersion with implanted silicone chains. Owing to its specific features the paint eliminates the phenomenon of the internal steam condensation sealing the filtering surfaces at the same time. The content of an agent resistant to weather conditions as well as erosion protects surfaces treated with the paint against formation of moss and lichen on the renovated and protected surfaces.

PREPARATION OF

FAST RENO-ROOF should be applied on bases which are dry, free from any dust and impurities, without lichen, moss and algae (in case they appear, they must be removed with **FAST DACH**). Depending on the base absorptivity it is recommended to apply **FAST GRUNT G** before painting.

PREPARATION AND

FAST RENO-ROOF is a ready for use paint. Apply a single coat with a brush or a roller or a sprayer at the temperature of from + 5°C to + 25° C. Depending on the absorptivity of the base it is allowable to dilute the paint up to 10% with water. Stir carefully before applying.

EFFICIENCY

The use of **FAST RENO-ROOF** depends on the base condition and the method of application and is approximately from 0,08 to 0,20 l/ dm³

STORAGE

Store in tightly closed packages at the temperature of from +5°C up to +35°C. Suitability for use: 24 months.

TECHNICAL SPECIFICATIONS

Temperature of the base: **from + 5°C to + 25° C**
Use of the base: **after 12 hours**

PACKAGES

Plastic buckets of 5 l and 10 l
Pallets: 440 in 5 l plastic buckets (80 items)
528 in 10 l plastic buckets (44 items)



FAST RENO-ROOF renovating-protecting roof paint



STANDARDS / NORMS

Sanitary Certificate issued by the State Sanitary Department no HK/B/ 2001/01/2002.

NOTE

The range of the product use recommended and defined in these instructions does not relieve the user/contractor from the obligation of carrying out works following both building principles as well as labour safety regulations.

P.W. FAST guarantees and shall be liable for the product quality, however it cannot control methods in which the product was used and under what conditions.